

CINNAMON




OVERVIEW

SPECIES	EUROPEAN OAK
SURFACE	BRUSHED
FINISH	UV OIL
GRADES	PRIME/RUSTIC/NATURE
STYLE	PLANK/HERRINGBONE
CONSTRUCTION	ENGINEERED
BACKING	BALTIC BIRCH WATER RESISTANT PLYWOOD
WEAR LAYER	15 mm (5/8") – 3,5 mm (0.14 in) 20 mm (3/4") – 5,5 mm (0.22 in)
THICKNESS	15 mm, 20mm (5/8", 3/4")
WIDTHS	PLANKS – 130 mm, 180 mm, 220 mm, 260 mm, 300 mm (5 1/8", 7", 8 5/8", 10 1/4", 12")
LENGTHS	PLANKS 600 mm – 3000 mm (2' – 10') PLANKS 600 mm – 2150 (2' – 7')
HERRINGBONE DIMENSIONS	130mm x 650 mm, 180 mm x 720 mm (5 1/8" x 25 19/32", 7" x 28 11/32")
EDGES	V4 or V2 micro

GRADING CRITERIA

PRIME	Grain is a variation of straight grain and medullary rays on boards. Colour fairly uniform. Flat Sawn. No sap allowed. Occasional healthy pin knots up to max 10mm. No cracks allowed.
NATURE	Grain is straight with natural grain variation allowed. Flat Sawn. No sap allowed. Healthy sound knots allowed up to 45mm. Black knots allowed up to 20mm. No cracks allowed.
RUSTIC	Grain can be straight and wavy. Natural colour variations. Flat Sawn. Kissing sap allowance 1-10%. Sound, healthy knots up to 60-70mm. Knots filled, all knots are small and not open. Black knots up to 30mm. End cracks allowed up to 10cm. Kissing Heart allowed.

Wood is a natural product. Each piece of wood is unique, therefore there will be variations in colour, quantity of knots and shade



ZENON Sp. z o.o. company reserves the right to change the specifications.

ZENON Sp. z o.o.
Ul. Ogrodowa 5
89-632 Brusy
POLAND
+ 48 52 398 23 47
enquiries@zenonfloors.com

