

## OVERVIEW

|                               |  |
|-------------------------------|--|
| <b>SPECIES</b>                | EUROPEAN OAK   |
| <b>FINISH</b>                 | UV LACQUERED   |
| <b>GRADES</b>                 | PRIME/RUSTIC/NATURE  |
| <b>STYLE</b>                  | PLANK/HERRINGBONE  |
| <b>CONSTRUCTION</b>           | ENGINEERED   |
| <b>BACKING</b>                | BALTIC BIRCH WATER RESISTANT PLYWOOD   |
| <b>WEAR LAYER</b>             | 15 mm ( 5/8" ) – 3,5 mm (0.14 in)<br>20 mm (3/4" ) – 5,5 mm (0.22 in)                |
| <b>THICKNESS</b>              | 15 mm, 20mm ( 5/8", 3/4" )   |
| <b>WIDTHS</b>                 | PLANKS – 130 mm, 180 mm, 220 mm, 260 mm, 300 mm ( 5 1/8", 7", 8 5/8", 10 1/4", 12" ) |
| <b>LENGTHS</b>                | PLANKS 600 mm – 3000 mm ( 2' – 10' )<br>PLANKS 600 mm – 2150 mm ( 2' – 7' )          |
| <b>HERRINGBONE DIMENSIONS</b> | 130mm x 650 mm, 180 mm x 720 mm<br>( 5 1/8" x 25 19/32", 7" x 28 11/32" )            |
| <b>EDGES</b>                  | V4 micro   |

## GRADING CRITERIA

|               |  |
|---------------|--|
| <b>PRIME</b>  | Grain is a variation of straight grain and medullary rays on boards. Colour fairly uniform. Flat Sawn. No sap allowed. Occasional healthy pin knots up to max 10mm. No cracks allowed.   |
| <b>NATURE</b> | Grain is straight with natural grain variation allowed. Flat Sawn. No sap allowed. Healthy sound knots allowed up to 45mm. Black knots allowed up to 20mm. No cracks allowed.  |
| <b>RUSTIC</b> | Grain can be straight and wavy. Natural colour variations. Flat Sawn. Kissing sap allowance 1-10%. Sound, healthy knots up to 60-70mm. Knots filled, all knots are small and not open. Black knots up to 30mm. End cracks allowed up to 10cm. Kissing Heart allowed. |

**Wood is a natural product. Each piece of wood is unique, therefore there will be variations in colour, quantity of knots and shade**



ZENON Sp. z o.o. company reserves the right to change the specifications.

ZENON Sp. z o.o.  
Ul. Ogrodowa 5  
89-632 Brusy  
POLAND  
+ 48 52 398 23 47  
[enquiries@zenonfloors.com](mailto:enquiries@zenonfloors.com)

