

## OVERVIEW

<b>SPECIES</b>	EUROPEAN OAK
<b>SURFACE</b>	BAND SAW
<b>FINISH</b>	UV OIL
<b>GRADES</b>	RUSTIC
<b>STYLE</b>	PLANK/HERRINGBONE
<b>CONSTRUCTION</b>	ENGINEERED
<b>BACKING</b>	BALTIC BIRCH WATER RESISTANT PLYWOOD
<b>WEAR LAYER</b>	15 mm ( 5/8" ) – 3,5 mm (0.14 in) 20 mm (3/4" ) – 5,5 mm (0.22 in)
<b>THICKNESS</b>	15 mm, 20mm ( 5/8" , 3/4" )
<b>WIDTHS</b>	PLANKS – 130 mm, 180 mm, 220 mm, 260 mm, 300 mm ( 5 1/8" , 7" , 8 5/8" , 10 1/4" , 12" )
<b>LENGTHS</b>	PLANKS 600 mm – 3000 mm ( 2' – 10' ) PLANKS 600 mm – 2150 (2' – 7')
<b>HERRINGBONE DIMENSIONS</b>	130mm x 650 mm, 180 mm x 720 mm (5 1/8" x 25 19/32" , 7" x 28 11/32" )
<b>EDGES</b>	V4 or V2 micro

## GRADING CRITERIA

### **PRIME**

Grain is a variation of straight grain and medullary rays on boards. Colour fairly uniform. Flat Sawn. No sap allowed. Occasional healthy pin knots up to max 10mm. No cracks allowed.

### **NATURE**

Grain is straight with natural grain variation allowed. Flat Sawn. No sap allowed. Healthy sound knots allowed up to 45mm. Black knots allowed up to 20mm. No cracks allowed.

### **RUSTIC**

Grain can be straight and wavy. Natural colour variations. Flat Sawn. Kissing sap allowance 1-10%. Sound, healthy knots up to 60-70mm. Knots filled, all knots are small and not open. Black knots up to 30mm. End cracks allowed up to 10cm. Kissing Heart allowed.

**Wood is a natural product. Each piece of wood is unique, therefore there will be variations in colour, quantity of knots and shade**



ZENON Sp. z o.o. company reserves the right to change the specifications.

ZENON Sp. z o.o.  
Ul. Ogrodowa 5  
89-632 Brusy  
POLAND  
+ 48 52 398 23 47  
[enquiries@zenonfloors.com](mailto:enquiries@zenonfloors.com)





Z E N O N

### **Cleaning and Maintenance Instruction**

### **COLOR – TIZIANO VINTAGE GRAY**

Zenon Flooring products with oil surfaces require periodic cleaning and care treatments . The frequency of treatments depends on its use, the amount of foot traffic, general wear and tear and cleaning frequency.

Rubio® MONOCOAT products ensure lasting protection and maintenance of your wood flooring. Below is a guideline:



### **RMC Soap**

RMC Soap is a maintenance soap intended for the regular cleaning of oil finished, wooden surfaces. The soap thoroughly removes any dirt and grease while maintaining the matte, natural look of the wood.

RMC Soap is very concentrated and hence very economical.



0% VOC



MAX. 50 À 100 ML/10 L WATER



MANUAL - INDUSTRIAL



BOTTLE: 1 L - 2 L



### **RMC Surface Care**

RMC Surface Care is the handy, ready to use version of RMC Soap. RMC Surface Care is suitable for fast cleaning of small floor surfaces and local spots on wooden floors, coffee tables, counter tops,...



0% VOC



MANUAL - INDUSTRIAL



ECOSPRAY: 750 ML



- › Clean maximum once a week with RMC Soap or RMC Surface Care. Cleaning too often or with too much RMC Soap or RMC Surface Care may leave a thin layer on the surface, which dirt and dust may adhere to.
- › Do not leave any water on the surface, a damp-clean is sufficient. Do not walk on the floor until it is completely dry.
- › The best working method is with two buckets: one with the soap mixture and one with clean water to rinse the dirt out of the mop.

How do I continue to keep my wooden surface clean?



**May be done frequently**



**Max. once a week**

Legend:



**CLEAN DRY**  
vacuum cleaner, Swiffer,.....



**RMC SOAP or RMC SURFACE CARE**

## › STAINS

Although many stains can be removed with RMC Soap and RMC Surface Care, Rubio® Monocoat also developed a number of specific stain removers. Stubborn lime stains can be handled effectively with RMC Limespot Remover, grease stains with RMC Grease Remover and black/tannin stains with RMC Tannin Remover. If the stain has penetrated the wood too deeply, the spot can be sanded and re-oiled.



### RMC Grease Remover

- › Grease stains  
e.g. olive oil, frying oil, crisps, oil, etc.
- › Also: heel marks and floor polish



MANUAL



30 MIN.



ECOSPRAY: 500 ML



### RMC Limespot Remover

- › Lime stains and other alkaline stains,  
e.g. urine, fertilizers, rust stains, radiator water, etc.
- › Also: white rings



MANUAL



30 MIN.



ECOSPRAY: 500 ML



### RMC Tannin Remover

- › Black/tannin stains e.g. rings/stains from cans, flower pots, etc.
- › Also:
  - After water damage on parquet.
  - In case of efflorescence on exterior wood (on the bottom of gates, doors, on walls).



MANUAL



30 MIN.



ECOSPRAY: 500 ML

#### TIPS:

- › After a treatment with RMC Limespot Remover, RMC Grease Remover or RMC Tannin Remover, you may need to apply some oil in the original colour on the spot.
- › If the surface becomes too stain-sensitive, maintain with RMC Oil Plus 2C (in the original colour applied) to repair both colour and protection.



## HOW TO HANDLE STAINS?



**RMC SOAP** or  
**RMC SURFACE CARE**

⋮  
If the stains have not disappeared,  
proceed to step 2.



**SPECIFIC STAIN REMOVERS**  
calcareous water stains, grease stains and  
black/tannin stains

⋮  
If the stains have not disappeared,  
proceed to step 3.



**RMC OIL PLUS 2C**  
Re-sand and oil locally

Legend:



RMC SOAP or  
RMC SURFACE CARE



RMC LIMESPOT  
REMOVER



RMC GREASE  
REMOVER




RMC TANNIN  
REMOVER



SPOT  
SANDING



RMC OIL  
PLUS 2C



Z E N O N